



Instructions:

- Before positioning your mag-motif ensure the surfaces of both the vehicle and magnet are clean and dry.
- To avoid uneven weathering of paintwork the mag-motif should be removed regularly, ideally once a week, cleaned, dried and repositioned.
- Avoid placing on heavily contoured body areas and ensure all edges are in contact with steel panels.
- When not in use keep flat, ideally on fridge front to avoid motif collecting ferrous dust.
- Do not use on re-painted surfaces as possible damage could occur.
- Do not use on panels which have been repaired with body filler.



copyright ©magmotif / Fullshire Ltd.

5 060040 325933

mag-motif

MAGNETIC FOOTBALL MOTIF



mag-motif

MAGNETIC FOOTBALL MOTIF



use time and time again • tested to 100mph • no adhesive • saves paintwork • low theft risk - looks like a sticker



mag-motif

MAGNETIC FOOTBALL MOTIF



use time and time again • tested to 100mph • no adhesive • saves paintwork • low theft risk - looks like a sticker





Instructions:

- Before positioning your mag-motif ensure the surfaces of both the vehicle and magnet are clean and dry.
- To avoid uneven weathering of paintwork the mag-motif should be removed regularly, ideally once a week, cleaned, dried and repositioned.
- Avoid placing on heavily contoured body areas and ensure all edges are in contact with steel panels.
- When not in use keep flat, ideally on fridge front to avoid motif collecting ferrous dust.
- Do not use on re-painted surfaces as possible damage could occur.
- Do not use on panels which have been repaired with body filler.



copyright ©magmotif / Fullshire Ltd.

5 060040 325933

mag-motif

MAGNETIC FOOTBALL MOTIF



...e time and time again • tested to 100mph • no adhesive - saves paintwork • low theft risk - looks like a sticker



Instructions:

- Before positioning your mag-motif ensure the surfaces of both the vehicle and magnet are clean and dry.
- To avoid uneven weathering of paintwork the mag-motif should be removed regularly, ideally once a week, cleaned, dried and repositioned.
- Avoid placing on heavily contoured body areas and ensure all edges are in contact with steel panels.
- When not in use keep flat, ideally on fridge front to avoid motif collecting ferrous dust.
- Do not use on re-painted surfaces as possible damage could occur.
- Do not use on panels which have been repaired with body filler.

copyright ©magmotif / Fullshire Ltd.

